


AEG

AT A CLOSER LOOK:
WHAT DOES IT TAKE
TO MAKE AN AEG MODULE?



LOOKING INTO AEG
QUALITY MANAGEMENT PROCESSES


AEG


WHAT MAKES AN AEG MODULE?

AEG solar modules are made to last, and to deliver safely clean energy to household, commercial and utility installations over their whole lifespan.

This is possible thanks to advanced product design, to the accurate selection of components, and to exacting manufacturing standards.

But what does it take to make an AEG module?





...HERE'S WHAT IT TAKES:



QUALIFIED SUPPLIERS

Solar Solutions only works with qualified suppliers who fulfill rigorous requirements. The assessment spans thorough bankability checks, back-to-back warranty capabilities, manufacturing capacity assessment, and process qualifications as issued by independent third-party certification bodies, including among others the standards Quality Management System ISO 9001, Environmental Management System ISO 14001, and Occupational Health and Safety OHSAS 18001.

Qualified suppliers must be authorized by Electrolux Group for the production of AEG solar modules, and undergo periodical inspections by the Solar Solutions Quality Control Team, the Electrolux Quality team and third party inspectors at all levels. The audited aspects include among others equipment calibration, traceability, production monitoring, documentation consistency, and purchasing processes.

- BANKABILITY
- MANUFACTURING CAPACITY
- BACK-TO-BACK WARRANTY
- CERTIFICATION ISO 9001
- CERTIFICATION ISO 14001
- CERTIFICATION OHSAS 18001
- ELECTROLUX & THIRD-PARTY ASSESSMENT

AEG






STATE-OF-ART MANUFACTURING FACILITIES

Suppliers qualifying for the production of AEG solar modules feature manufacturing facilities with highest automation levels reaching up to 95% and state-of-the-art manufacturing equipment with clear SOPs (Standard Operating Procedures) for each function and workstation, maintenance plans, criteria and records; and consistently trained personnel.

AEG





CAREFULLY SELECTED COMPONENTS

Solar Solutions works in close cooperation with suppliers to select high quality components that are tested and certified to guarantee a solid product able to withstand demanding environmental challenges.

We constantly strive to offer those technologies that have proven reliable in granting solar yields, and at the same time to optimize product design introducing new features to increase stability and efficiency -from PERC to multibusbar from half-cut cells to double glass.

While proven technical reliability is the core of the component selection, we ensure that these components grant each AEG module a perfect optical look. Choosing for instance glass, busbars and backsheets in ultra black to grant an elegant and seamless total look.

AEG





CERTIFIED PROCESSES

The manufacturing process of AEG solar modules underlies exacting international standards which grant consistency in product quality and looks, and, ultimately, safety to the end customer.

AEG products are certified according to the standards of IEC 61215 and IEC 61730-1/2 (2005 / 2016 recast).

Certifying against the IEC 61215 standard means ensuring the long-time reliability of the modules. Modules undergo accelerated stress tests- thermal, damp heat, humidity freeze cycles, as well as UV, static and dynamic mechanic load tests that are meant to evaluate the bounty of the module design against environmental stressors that could impair the module functioning in the field.

With the IEC 61730-1/2 certification, the focus lies on the safety requirements. The modules undergo exigent endurance tests against electrical shock hazard, fire hazard, and for mechanical and structural safety.

AEG solar modules are further tested according to local requirements of the specific markets and registered to the relevant national accreditation bodies.

Among the independent certification and accreditation bodies testing AEG solar modules are TÜV Süd, TÜV Rheinland, KIWA, CSI laboratories, etc.

CSI (Certificate of Conformity) - IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016

kiwa (KIWA) - IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016

TÜV SÜD (TÜV SÜD) - IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016

TÜV RHEINLAND (TÜV RHEINLAND) - IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016

CERTIFICATE No. Z2 099312 0048 Rev. 00
 Holder of Certificate: Solar Solutions GmbH
 Brückenstraße 94
 60394 Frankfurt am Main

Zertifikat / Certificate
 Zertifikat Nr. / Certificate No. PV 50463583
 Blatt / Sheet 0002

Ihre Zeichen / Client Reference: M
Unser Zeichen / Our Reference: 01-279-50114900 017
Anstellungsdatum / Date of Issue: 15.04.2022
IdNr./No.: 660/Rev00

Gesamthaltiger Lizenzhaber / License Holder: Solar Solutions GmbH
 Brückenstraße 94,
 60394 Frankfurt am Main
 Germany

Freigelegte Manufacturing Plant: 040-002286393

Prüfzeichen / Test Mark: IEC 61215-1:2016, IEC 61215-2:2016, IEC 61730-1:2016, IEC 61730-2:2016, EN 61215-1:2016, EN 61215-2:2016, EN IEC 61730-1:2016, EN IEC 61730-2:2016

Zertifiziertes Produkt / Certified Product: PV Module
 Continued on Page 1
 Misch. W out of mono Si-cells:
 AS-M443B-W-XXX (XXX-330-430, in steps of 5, 144 cells)
 AS-M425B-W-XXX (XXX-276-365, in steps of 4, 120 cells)
 Misch. W out of poly Si-cells:
 AS-P1441-W-XXX (XXX-310-420, in steps of 5, 144 cells)
 AS-P1201-W-XXX (XXX-260-335, in steps of 5, 120 cells)
 Misch. W out of mono Si-cells:
 AS-M443-W-XXX (XXX-330-420, in steps of 5, 144 cells)
 AS-M425-W-XXX (XXX-276-365, in steps of 5, 120 cells)
 Trademark: AEG


Lizenzgebühr - Einheit / License Fee - Unit:

TÜV RHEINLAND LGA Products GmbH, Tillystraße 2, 50431 Nürsberg
 Tel: +49 221 890-227, www.tuev-rheinland.de
 Fax: +49 221 890-3019, http://www.tuev-rheinland.de

Dipl.-Ing. CHG, Dipl.-Kaufm.

10 STEPS TO MODULE PRODUCTION

1. CELLS SOLDERING → 2. LAY-UP → 3. FIRST EL TEST AND VISUAL INSPECTION →
4. LAMINATION → 5. FRAMING AND JUNCTION BOX MOUNTING → 6. CURING →
7. CLEANING → 8. SAFETY TEST → 9. FLASH TEST → 10. SECOND EL TEST





CONSTANT QUALITY MONITORING

An AEG solar module is „under the lens“ from its very inception with in-line and offline quality monitoring.

It starts with thorough visual inspection of cell quality and their 7-level classification; it continues with the use of layout machines for consistent allineation of cells and ribbons throughout the whole production; a first electroluminescence tests (EL) is taken after layup to examine the cell and interconnection consistency. The production is in full swing, yet technicians carefully carry out hourly basis checks of the soldering machine temperature and calibrate the equipment every two hours. Every aspect of the module is taken under the lens through visual inspections aided by high resolution cameras and mirrors; the module is then flashed to ensure that its outputs match the required specifications; and a further electroluminescence test is taken to ensure full product integrity.

Each and every step is regulated by a detailed list of Quality Assurance criteria which determine if the product qualifies as AEG solar module; compliance to these criteria is regularly verified by the Solar Solutions Quality Team.

After successfully passing this scrutiny, the AEG solar module is labelled with the AEG Quality Control Seal.



The AEG module is then carefully packed within a sturdy box, tightly wrapped with straps to ensure safe transportation on the pallets.

From here, through the hands of our selected and reliable partners of the AEG solar distribution network, the AEG solar modules reaches the rooftops of customer homes and project sites to start its mission of delivering clean energy for its lifespan of 30 years and beyond.

The file „AEG_Cardboard example_general.pdf“ consists of two pages. The first one represents the position


Quality Management Processes Electroluminescence Inspection Criteria
Version: Dec 2019

AEG Solar Solutions GmbH · Brückenstrasse 94 · 65994 Frankfurt · Deutschland / Germany

Quality Management Processes
Visual Inspection Criteria 质量管理流程视觉检验标准
Version: March 2017

No.	Item 项目	Inspection Tool / Method 检测工具/方法	Value/Size of Inspection Criteria 检测标准/限值/尺寸
1	Cell colour 电池片颜色	Visual inspection 目视 Inspect module 2 meters away with the condition that UV-A is disconnected visual quality of inspection should be above 12. 目视检查模块的（未校正的）颜色，应高于12。	Contiguous colour of cells in a module is allowed. For example light blue and blue. The shade of nonadjacent colour in a module are not allowed. For example light blue and dark blue. 不允许同一组件中出现两种不相容的颜色。相邻浅蓝色和深蓝色。
2	Cell types 电池片类型/规格	Visual inspection 目视	No broken crystal and dirty crystal cells in the module. 组件内多晶硅电池片不允许有一个碎片。
3	Cell breaks 电池片裂痕	Visual inspection 目视	No breaks allowed 不允许
4	Cell cracks 电池片裂纹	Visual inspection 目视	No cracks allowed 不允许
5	Cell edge damage 电池片边缘损伤	Visual inspection with steel ruler 目视	No cell chipping is allowed 不允许 V shape indentation at the cell edge is not allowed. If shape indentation with the following specification is allowed: Length > 2mm, Depth > 1mm, less than 2 damaged edges in 1 cell. Cell Gap: Less Than 2mm per module.
6	Cell layout 电池片排列	Visual inspection with steel ruler 目视	Cell Gap: defined between cell on edge: 2 ± 0.5 mm Horizontal / Vertical cell dislocation 1 mm Distance from both nearest edges of cells columns to the edge of glass is 4.5 mm. Distance from both nearest edges of cells columns to the edge of glass is no more than 5mm. 横向/纵向电池片的间距: 2 ± 0.5 mm 从电池片边缘到玻璃边缘的距离: 4.5 mm 从电池片边缘到玻璃边缘的距离: 不大于 5mm
7	Bottom mark 电池片上标识	Visual inspection with steel ruler 目视	Length: 4.0 mm and depth: 1.0 mm

AEG



Solar Solutions GmbH
Brückenstrasse 94
60594 Frankfurt am Main
Germany

www.aeg-industrialsolar.de
info@aeg-industrialsolar.de

AEG is a registered trademark used under license from Electrolux AB (publ).